

Tableau de rechargement 38 Special

| PROJECTILE BULLET | | | ETUI CASE | AMORCAGE PRIMER | POUDRE/POWDER VECTAN | | | VITESSE 2,5 m VELOCITY | | PRESSION PRESSURE | | NORMES CIP | |
|---------------------------|--------------|--------|--------------|-----------------|----------------------|---------|--------|------------------------|--------|-------------------|-------|------------|------------------|
| TYPE | POIDS/weight | | | | TYPE | CHARGE | | m/s | f/s | bars | psi | LONGUEUR | PRESSION Crusher |
| | Grammes | grains | | | | Grammes | grains | | | | | | |
| Speer JSP-FN | 8.10 | 125.0 | Norma | CCI 500 | Ba9 | 0.42 | 6.5 | 325.0 | 1066.0 | 1200 | 17400 | 29.34 | 1500 |
| Lynx coulé HR P-915-SWC | 9.30 | 144.0 | Remington | CCI 500 | Ba10 | 0.24 | 3.7 | 275.0 | 902.0 | 1200 | 17400 | 29.34 | 1500 |
| Lynx coulé HR P-915-SWC | 9.30 | 144.0 | Remington | CCI 500 | AS | 0.24 | 3.7 | 255.0 | 836.0 | 750 | 10900 | 29.34 | 1500 |
| Lynx coulé HR P-915-SWC | 9.30 | 144.0 | Remington | CCI 500 | A1 | 0.32 | 5.0 | 270.0 | 885.0 | 700 | 10100 | 29.34 | 1500 |
| Lynx coulé HR P-915-SWC | 9.30 | 144.0 | Remington | CCI 500 | Ba9 | 0.44 | 6.8 | 320.0 | 1049.0 | 1000 | 14500 | 29.34 | 1500 |
| Norma Plomb RB-Base plein | 10.20 | 158.0 | Hirtenberger | CCI 500 | Ba10 | 0.25 | 3.8 | 270.0 | 885.0 | 1200 | 17400 | 29.34 | 1500 |

| | | | | | | | | | | | | | |
|---------------------------|-------|-------|--------------|----------|------|------|-----|-------|--------|------|-------|-------|------|
| Norma Plomb RB-Base plein | 10.20 | 158.0 | Hirtenberger | CCI 500 | Ba9 | 0.38 | 5.8 | 300.0 | 984.0 | 1000 | 14500 | 29.34 | 1500 |
| Norma Plomb RB-Base plein | 10.20 | 158.0 | Hirtenberger | CCI 500 | A1 | 0.32 | 5.0 | 280.0 | 918.0 | 800 | 11600 | 29.34 | 1500 |
| SFM Blindé | 10.20 | 158.0 | SFM | NCS 1113 | Ba9 | 0.48 | 7.4 | 280.0 | 918.0 | 1200 | 17400 | 29.34 | 1500 |
| SPEER HP | 10.20 | 158.0 | Federal | CCI 500 | Ba9 | 0.34 | 5.2 | 270.0 | 885.0 | 1000 | 14500 | 29.34 | 1500 |
| SIERRA HP 8360 | 10.20 | 158.0 | Norma | CCI 500 | A1 | 0.35 | 5.4 | 270.0 | 885.0 | 960 | 13900 | 29.34 | 1500 |
| SIERRA HP 8360 | 10.20 | 158.0 | Norma | CCI 500 | AS | 0.32 | 4.9 | 260.0 | 853.0 | 1000 | 14500 | 29.34 | 1500 |
| Norma RN Plomb | 10.20 | 158.0 | Norma | CCI 500 | Ba9 | 0.40 | 6.0 | 290.0 | 951.0 | 850 | 13300 | 29.34 | 1500 |
| Norma RN Plomb | 10.20 | 158.0 | Norma | CCI 500 | A1 | 0.38 | 5.8 | 290.0 | 951.0 | 810 | 11700 | 29.34 | 1500 |
| SFM-Plomb | 10.20 | 158.0 | SFM | NCS 1113 | Ba10 | 0.25 | 3.9 | 245.0 | 803.0 | 850 | 13300 | 29.34 | 1500 |
| Lynx coulé HR no P 917 | 10.20 | 158.0 | Remington | CCI 500 | AS | 0.22 | 3.4 | 250.0 | 820.0 | 720 | 10400 | 29.34 | 1500 |
| Lynx coulé HR no P 917 | 10.20 | 158.0 | Remington | CCI 500 | Ba9 | 0.37 | 5.7 | 310.0 | 1017.0 | 1100 | 15900 | 29.34 | 1500 |

| | | | | | | | | | | | | | |
|----------------------|-------|-------|-----|----------|-----|------|-----|-------|-------|-----|-------|-------|------|
| SFM 1/2 blindé | 10.35 | 160.0 | SFM | NCS 1113 | Ba9 | 0.41 | 6.3 | 230.0 | 754.0 | 810 | 11700 | 29.34 | 1500 |
|----------------------|-------|-------|-----|----------|-----|------|-----|-------|-------|-----|-------|-------|------|